

	    				
	RG-NBS5100-48GT4SFP	RG-NBS5100-24GT4SFP	RG-NBS5200-24GT4XS	RG-NBS5200-24SFP/8GT4XS	RG-NBS5200-48GT4XS
10/100/1000Base-T ports	48	24	24	8 combo	48
SFP (1G)	4	4	-	24	-
SFP+ (10G)	-	-	4	4	4
Switching capacity	104 Gbps	56 Gbps	128 Gbps	128 Gbps	176 Gbps
Forwarding rate	78 Mpps	42 Mpps	96 Mpps	96 Mpps	132 Mpps
MAC address table	16000	16000	16000	16000	16000
VLAN range	4094	4094	4094	4094	4094
Dimensions (W x D x H)	440 mm x 267.5 mm x 43.6 mm	440 mm x 207.5 mm x 43.6 mm	440 mm x 207.5 mm x 43.6 mm	440 mm x 267.5 mm x 43.6 mm	440 mm x 267.5 mm x 43.6 mm
Weight (With package)	3.6 kg	2.9 kg	2.9 kg	3.35 kg	3.6 kg
Jumbo Frame (MTU)	9216	9216	9216	9216	9216
Link Aggregation Group (LAG)	16	16	16	16	16
ACL	1900	1900	1900	1900	1900
STP/RSTP	✓	✓	✓	✓	✓
Auto Errdisable Recovery	✓	✓	✓	✓	✓
Voice VLAN	✓	✓	✓	✓	✓
LLDP/LLDP-MED	✓	✓	✓	✓	✓
IGMP Snooping v1/v2	✓	✓	✓	✓	✓
CPP	✓	✓	✓	✓	✓
EEE	✓	✓	✓	✓	✓
Power supply	Fixed, 100 - 240V AC, 2A	Fixed, 100 - 240V AC, 1.5A	Fixed, 100 - 240V AC, 1.5A	Fixed, 100 - 240V AC, 2A	Fixed, 100 - 240V AC, 2A
Fan	✓	✓	✓	✓	✓
Airflow	Left/Right-to-Rear	Left-to-Rear	Left-to-Rear	Left-to-Rear	Left/Right-to-Rear
Port surge	6 kV	6 kV	6 kV	6 kV	6 kV
MTBF	> 200,000	> 200,000	> 200,000	> 200,000	> 200,000